

MVE CryoSystem 6000 Full Auto

With the TEC 3000

The MVE CryoSystem 6000 Full Auto combines the compact efficiency of aluminum dewars with the monitoring and auto fill features of the TEC3000 control system. The TEC3000 continually monitors and records temperature and LN_2 levels, auto filling when needed, and providing audio/visual alarms with remote connectivity when necessary. The enhanced safety factor of not having to manually fill this unit also helps maintain a consistent temperature profile.

The CryoSystem 6000 Full Auto provides the convenience and security of high capacity stainless steel freezers for your average sized sample collection at a fraction of the price.

Key Features

- Fully automatic LN₂ level control and temperature monitoring
- Designed for liquid storage.
- 17 user-defined audio / visual alarms
- Newly designed, durable lid
- Controller post tilted for convenient LCD viewing
- Easily moved in case of emergencies or in the of event of natural disasters
- Includes six racks, transer hose, and roller base




MVE CryoSystem 6000 Full Auto

Performance			
• LN ₂ Capacity w/o Inventory L est.	175.0		
• Static Evaporation Rate* L/day	2.5		
Unit Dimensions			
• Neck Opening in. (mm)	8.5 (216)		
• Overall Height with Auto Fill in. (mm)	37.9 (963)		
• Outer Diameter in. (mm)	26.5 (673)		
• Weight Empty lb. (kg)	156 (70.7)		
o Weight Full Ib. (kg) est.	478 (216.8)		
Maximum Storage Capacity			
 Box Size in. Standard box side is 2 inches. Additional sizes available. 	2	3	3.75
• Number of Racks	6	6	6
• Number of vials 1.2 & 2 ml vials 100/box est.	6,000	4,200	3,000
o Boxes per Rack	10	7	5

* Static evaporation rate and static holding time are nominal. Actual rate and holding time will be affected by the nature of container use, atmospheric conditions, and manufacturing tolerances.

THREE Year Vacuum Warranty • TWO Year Parts Warranty

Conforms to MDD 93/42/EEC, the Medical Device Directive for the EU.



ML-000019 Rev 0

© 2024 MVE Biological Solutions reserves the right to discontinue its products, or change the prices, materials, equipment, quality, descriptions, specifications and/or processes to its products at any time without prior notice and with no further obligation or consequence. All rights not expressly stated herein are reserved by us, as applicable.

